



# JM-VL02

LTE Cat M1 & NB2 Fleet Tracker



The JM-VL02 is designed to handle industrial and commercial fleet applications ranging from rental agencies and public transportation to construction equipment and beyond. With ACC detection, SOS button, remote fuel/power cutoff, and various other I/Os for peripherals, this powerful device can be customized to streamline your operations and boost efficiency. And, using cutting-edge LTE (Cat M1/NB-IoT) and GSM communications, the VL02 will be helping you maximize your fleet operations for years to come.



### LTE Cat M1/NB2 & GSM

The device can receive and transmit data in the coverage of 4G and 2G network.



### Remote Cut-off (Fuel/Power)

Immobilize a vehicle by cutting off its power source/fuel supply through an installed relay.



### Ignition Detection

Always keeps you informed of the ACC status of your vehicle.



### Panic Button

A button close to driver allowing him to ask for immediate help with just a single press.



### Door Status Detection

You'll be quickly notified when vehicle door has been illegally opened.



### Fuel Sensor/ Temperature Sensor (Optional)

Prevents fuel theft and leakage, also the damage to goods caused by abnormal temperature.



### RFID Reader (Optional)

Identify drivers when they start vehicles, and collect and upload the drivers' identification.



### Multiple Alerts

Instant alerts of typical events such as vibration, towing, geo-fence, speeding, etc.

#### Fleet Management



#### Construction Machinery Monitoring



#### Public Transport



## GNSS

Positioning system	GPS+LBS
Frequency	L1
Positioning accuracy	<2.5m CEP
Track sensitivity	-165dBm
Acquisition sensitivity	-148dBm
TTF (open sky)	Avg. hot start ≤ 1sec Avg. cold start ≤ 32sec

## Cellular

Communication network	LTE/GSM
Frequency	<b>JM-VL02A:</b> LTE Cat-M1/NB2: B1/B2/B3/B4/B5/B12/B13/B28/B66 GSM: 850/900/1800/1900 MHz <b>JM-VL02E:</b> LTE Cat-M1/NB2: B1/B3/B5/B8/B18/B19/B20/B26 GSM: 850/900/1800/1900 MHz

## Power

Battery	300mAh/3.7V industrial-grade Li-Polymer battery
Input voltage	9-36VDC

## Interface

LED indication	GNSS (Blue), Cellular (Green), Power (Red)
SIM	Standard-SIM
Data storage	32+32Mb
Digital inputs	ACC, SOS, input
Digital outputs	Relay, output

## Physical specification

Dimensions	105.5 x 57.0 x 21.8mm
Weight	104g

## Operating environment

Operating temperature	-20°C to +70°C
IP rating	IP65

## Feature

Sensors	Accelerometer
Scenarios	Vehicle movement alert, Over-speed alert, Geo-fence, Vehicle battery detection, Power supply disconnection
Driving behavior analysis	Harsh acceleration, Harsh braking, Harsh cornering, Collision